

Project:	
Location:	
Item #:	Quantity:
Model #:	

MODEL: ICT-VIP1740B1/3GLASSTOP

COUNTER TOP:

Refrigerated ingredient displays - Glass top

Important: Do only introduce refrigerated products! For daily cleaning, remove products and

disconnect unit.



General Strengths

- Sanitation. The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- Control systems. Higher precision in managing temperature settings. Greater ability to adjust temperature ranges as per the end user's requirement.
- 100% Tested. All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- Certified. Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)

MODEL		Dimension inches) (mr		Nº Doors	Nº Pans Ref.	Ref.	Ref. Weight	Temp. Range	Capacity (Cu. Ft.)	Cond. Unit.	Case Amps	Crated Weight
	W	D	Н	Doors			(Lbs.) (gr.)	(°F) (°C)	(L)	H.P.	115 V.	(Lbs.) (Kg.)
ICT-VIP1740	68-1/4	16-1/4	17-3/4	_	6	R134a	0.53	39°F/41°F	1.83	1/6	1.82	146
B1/3glasstop	1733	413	450				240	4ºC/6ºC	52			66

Infrico USA Corp.

7042 N.W. 46th Street

Miami, FL 33166

1.305.777.9599 Office 1.305.777.9598 Fax

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE









www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:



Project:	
Location:	
Item #:	Quantity:
Model #	

MODEL: ICT-VIP1740B1/3GLASSTOP

COUNTER TOP:

Refrigerated ingredient displays - Glass top

STANDARD FEATURES

Exterior

- AISI 304 Stainless Steel.
- Safety glass on the top, closed in the front (facing the customer) and open in the back (facing the operator),
- Sliding doors on the back,
- Levelling feet.

> Interior

- AISI 304 Stainless Steel,
- Sealed interior floors and rounded cabinet corners,
- Stainless steel 6" deep pans, included.

Insulation

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in place using a high density polyurethane insulation,
- Low GWP & Zero ODP effect.

Refrigeration

- Digital temperature controller with automatic defrost system,
- Cold wall refrigeration system,
- Refrigeration capacity: 973 Btu/h (14°F) / 190 W (-10°C).

Electrical

- Cord and NEMA 5-15P plug.
- Electrical connection is 115V / 1ph / 60 Hz



ETL Listed to UL471 Standard and Sanitation classified to NSF7.

OPTIONAL FEATURES


✓ Electrical connection is 220-230 V / 1ph / 50 Hz (plug type varies).

PLAN VIEW

68¼" [1733mm] 161/4" [413mm] [307m

ELEVATION

RIGHT VIEW



PLAN VIEW

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE











Infrico USA Corp. 7042 N.W. 46th Street Miami, FL 33166 1.305.777.9599 Office

1.305.777.9598 Fax

www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:

