

SUWANNEE COUNTY SCHOOL BOARD
INVITATION TO BID #17-212
"New Mobile Kitchen/Food Trailer"

Scope of Work: Suwannee County School Board is seeking bids from dealers or individuals for the purchase of a new Mobile Kitchen/Food Trailer. The services to be provided under this bid include, but are not limited to meeting the minimum criteria as requested below:

1. 8'6" wide x 20' long Trailer Manufacturing Mobile Kitchen Trailer
2. Custom reinforced walk on roof
3. Two - pairs of heavy duty scissor type stabilizer jacks located on front & rear of trailer, 5000 lb static load capacity each
4. Extended three piece 'A' frame (5' long tongue) with a heavy duty tongue jack & sand pad
5. 2 5/16" top mount coupler with replaceable locking dog assembly
6. D.O.T. compliant 5/16" safety chains with Clevis safety slip hook & latch
7. 6"x2" rectangular steel tube main rails with equal height 'C' section cross members with square outriggers & steel side plates - steel cross members on 16" center
8. Two - 6000 LB (12,000 GVWR) 10 degree up torsion axles with 12" x 2" electric brakes, E/Z lube & 8 on 6.5 hubs and drums with weather resistant wiring package
9. Four - ST235/80R16 load range 'E' radial tires mounted on an 8 bolt electro deposition coated silver bullet hole wheel
10. Chassis fully under coated with CPC (Corrosion Preventative Compound)
11. 7' interior height
12. Custom curbside 3 section TEMPERED GLASS SERVING WINDOW (45" high x 69" wide), with 1 display/picture window & 2 vertical slider windows with screens (16" mesh) that will serve customers – lift up awning (approx. 113" wide) with 2 keyed flush locks for security & gas assist awning rods to raise & secure awning in upright position
13. 36" wide lockable pre-framed rear entry door with screen (16" mesh), flush lock & integrated dead bolt – Note: door opening should be as close to C/S counter as possible
14. ¾" exterior grade plywood floor
15. Non-porous and easily cleanable one piece heavy duty commercial grade RTP (Rubber Tread Plate) flooring over exterior grade plywood floor
16. Smooth and easily cleanable non-porous white aluminum ceiling liner with no exposed utility lines, piping, conduit or wiring – bonded for a smooth look
17. Smooth and easily cleanable non-porous white aluminum interior sidewall liner with no exposed utility lines, piping, conduit or wiring – bonded for a smooth look
18. Fully insulated sidewalls and ceiling
19. 84" long white laminated interior overhead cabinet with latching cabinet doors along curbside wall above the sink assembly
20. 12" deep x 122" long white aluminum interior overhead storage tray/shelf along curbside wall
21. 12" deep x 138" long white aluminum interior overhead storage tray/shelf along roadside wall
22. 24" deep x 122" long x 30" high interior counter along curbside wall – Note: cover top with stainless steel
23. Custom 18" deep x 122" long x approx 12" high interior underneath shelf below C/S

counter along curbside wall – Note: cover top with stainless steel

24. Custom 10" deep x 69" long stainless steel exterior fold down condiment counter in front of curbside serving window
25. 100 amp, 120/240v service panel/box with a 100 amp main breaker, approximately 20' long shoreline power cord for electrical connection and through floor cable hatch to run power cord outside – CRITICAL: balance panel/legs accordingly --- Note: mount panel along rear wall toward R/S above work top table
26. Twelve - 20 amp, 120v GFI duplex wall receptacles – Note: use cord drops where applicable
27. Three - 4' double fluorescent light fixtures with diffuser covers - include on/off light switch)
28. Three - single exterior weatherproof halogen floodlights on a GFI breaker – include interior on/off wall switch
29. Custom 24" deep x 84" long x 36" high white laminated enclosure/cabinet with latching cabinet doors for commercial NSF APPROVED stainless steel 3 compartment "Deli" sink with single faucet & integrated drain boards on each side (bowl size approx. 10x14x10) - include separate stainless steel hand sink & faucet with divider/splash guard to separate the hand sink from the 3 compartment sink - all sinks should have hot & cold running water under pressure – NOTE: cover top with stainless steel
30. Removable cutting board (NSF or equal) to place over the 3 compartment sink
31. On demand water pump with on/off wall switch
32. 40 gallon fresh water tank (NSF or equal) located under the sink assembly concealed in custom cabinet enclosure for a clean and professional look - 1/2" hot and cold NSF Pex water lines
33. 6 gallon, 120v hot water heater located under the sink cabinet/enclosure
34. Exterior water hook up with back flow preventer - include keyed locking door
35. 50 gallon waste water holding tank located under the trailer lower and away from the fresh water tank per regulatory requirements - include waste vent stack, 1 1/2" PVC drain lines & back flow preventer per code (Note: waste tank should be 15% larger & or greater than water tank)
36. A dump valve located under the trailer for easy waste removal
37. .030 pre-finished "WHITE" exterior aluminum "BONDED"
38. Aluminum teardrop fenderettes over wheel wells
39. 120v, 15,000 BTU roof mounted air conditioner with a 5600 BTU heat strip
40. 14"x14" screened (16" mesh) translucent roof vent with crank – include a roof vent cover for rain protection while vent is open
41. S.A.E. color coded 12v electrical system, D.O.T. required exterior lighting package
42. D.O.T. 'A' frame (tongue) mounted battery with breakaway switch
43. 7 way round trailer end connector (7 way RV blade style)
44. Custom anodized front and rear corner covers
45. Four - chrome ABS hub covers and trim rings
46. Honda 10KW gasoline standby generator - include

In addition to the trailer, the following equipment must be included

1. NSF APPROVED 19 cu. ft. standard commercial stainless steel stand up refrigerator (SW) – Note: Left Hand Hinge
2. NSF APPROVED 36" commercial stainless steel refrigerated sandwich prep unit with top

pans, lid and cutting board (BA)

3. NSF APPROVED 9 cu. ft. commercial counter top glass door display refrigerator manufactured by True, model GDM-9-LD
4. Two - NSF APPROVED commercial insulated hot holding cabinet/proofers with clear Lexan door
5. NSF APPROVED 60" long x 30" deep commercial stainless steel work top table with an adjustable underneath shelf
6. NSF APPROVED 72" long x 30" deep commercial stainless steel work top table with an adjustable underneath shelf
7. Paper towel holder and soap dispenser next to the hand sink
8. ABC fire extinguisher

Please include pictures of similar Mobile Kitchen/Food Trailers that your company has completed for other school districts or businesses.