## Safety Data Sheet

# 40703 Mötsenböcker's LIFT OFF ® Tape Remover



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

### 1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538 Product Name: Mötsenböcker's LIFT OFF ® Tape Remover

Product Code: 40703

Product Use: Spot Remover

24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

#### 2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols

GHS Classification Skin Sensitisation Category 1

Aspiration Hazard Category 1

Signal Word Dange

**Hazard Statements** May be fatal if swallowed and enters airways.

May cause an allergic skin reaction.

**Precautionary Statements** 

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.

P302+P352 - If on skin: Wash with plenty of soap and water.

P321 - Specific treatment (see on this SDS).

Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

 COMPONENT
 CAS #
 Percent

 Distillates (petroleum), hydrotreated light
 64742-47-8
 80 - 100

 2-propanone
 67-64-1
 1-20

 Methylal
 109-87-5
 1-20

 Fragrance
 Mixture
 0.1- 0.99

HMIS® III\* HAZARDOUS WARNINGS:

Health: 2 Flammability: 2 Physical: 0 Personal See Section 8

Protective Equipment:

<sup>\*</sup> See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

#### 4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: Wash the contaminated skin with soap and water. Wash clothing before reuse. Seek medical attention if symptoms persist. Seek

medical attention if symptoms persist.

Ingestion: Contact a physician, medical facility, or poison control center immediately. Aspiration into the lungs can cause serious damage. If

vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Do not induce vomiting.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until

help arrives or the victim starts to breathe on his own. Do not leave victim alone.

#### NOTES TO PHYSICIAN:

Aspiration during swallowing or vomiting may severely damage the lungs. This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system;

#### 5. FIRE FIGHTING MEASURES

Fire Fighting Instructions: Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may

be used from a safe distance to cool closed containers and protect surrounding area.

#### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

If runoff occurs, notify authorities as required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Avoid breathing vapors. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area.

#### 7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. If ventilation is not sufficient, wear proper respiratory equipment. Do not store containers in excessive heat

or direct sunlight. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Protect container

against physical damage. Use with adequate ventilation. Wash hands thoroughly after handling.

Storage: Keep container tightly closed when not in use. Empty container may contain residues which are hazardous. Store in a cool dry place.

Normal precautions common to safe manufacturing practice should be followed in handling and storage.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from

known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be

exceeded.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as

chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or

airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with

skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. If the possibility exists that

aerosols or mists may be inhaled while handling or processing this material, the use of a NIOSH/MSHA approved dust, fume, and mist respirator designed as respiratory protection against dust, fumes, and mist of materials having an exposure

limit of less than 0.05 mg/m3 is recommended.

COMPONENT CAS# ACGIH TLV OSHA PEL OTHER

Distillates (petroleum), hydrotreated light 64742-47-8 TWA: 200 mg/m³, (as Not established Not established

total hydrocarbon vapor) 8 hours

2-propanone 67-64-1 500 ppm TWA Not established Not established

Methylal 109-87-5 Not established 1000 ppm; 3100 mg/m3 Not established

8h TWA

Fragrance Mixture Not established Not established Not established

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:Bulk liquidLower Flammability Limit (%):Not applicableAppearance:Clear ColorlessUpper Flammability Limit (%):Not applicableOdor:CitrusVapor Pressure (PSIG @ 70°F):Not determined

Odor Threshold: Mild Vapor Density [air = 1]: >1 pH: Not applicable Relative Density (H2O=1): 0.8

Melting/Freezing Point (°F): No data available Solubility in Water: Not determined

Boiling Point (°F): No data available Partial Coefficient: n- No data available

octanol/water:

Flash Point (°F PMCC): 201.2 Autoignition Temperature (°F): Not applicable Evaporation Rate: Not determined Decomposition Temperature (°F): No data available Flammability (solid, gas): No data available Viscosity, dynamic (cSt): No data available

Percent VOCs (%): < 3

### 10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Oxidizers. Avoid contact with: Acids. Strong oxidizing agents.

Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Decomposition Products:

#### 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental No data available.

Toxicity:

2-propanone

Ingredient CAS# **Toxicological Data** 

Distillates (petroleum), hydrotreated light 64742-47-8 Dermal LD50 Rabbit > 2000 mg/kg

Oral LD50 Rat > 5000 mg/kg67-64-1 Dermal LD50 Rat > 7426 mg/kg

Oral LD50 Rat = 5800 mg/kg

Inhalation LC50 (4h) Rat > 76 mg/L Dermal LD50 Rabbit > 5000 mg/kg Methylal 109-87-5

Oral LD50 Rat = 6423 mg/kg

## 12. ECOLOGICAL INFORMATION

**Ecological Toxicity:** No data available Mobility: No data available Degradability: No data available.

Ingredient CAS# **Toxicological Data** 

Aquatic LC50 (48h) Rainbow Trout = 6100 mg/L 2-propanone 67-64-1

48HR EC50 Daphnia = 7630 mg/L Aquatic LC50 (96h) Fish >= 1000 mg/L Methylal 109-87-5 48HR EC50 Daphnia >= 1200 mg/L

#### 13. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

### 14. TRANSPORTATION INFORMATION

**UN Number Hazard Class Packing Group Proper Shipping name** Agency

DOT Not regulated by agency **IATA** Not regulated by agency **IMDG** Not regulated by agency

#### 15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT % BY WEIGHT **Regulatory Body** CAS# SARA Section 313 No components listed in this section.

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

## 16. OTHER INFORMATION

Other Information: SDS Prepared by L. Dean Swartz, SDS Coordinator

12/29/15 Version Date:

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.