unisource<sup>®</sup> MATERIAL SAFETY DATA SHEET 261/4119421



## ITEM NUMBER: U22996

VERSION 4 EFFECTIVE DATE: 8/29/05 SUPERCEDES: 8/9/01 PREPARED BY: Regulatory Compliance

Sections Revised: II, III, VI, IX

IDENTITY (As Used On Label and List): Blitz Airborne Flying Insect Killer

# EMERGENCY MEDICAL Telephone# 1-888-660-6737

PRODUCT HAZARD RATINGS (NFPA): Health = 1, Fire = 2, Reactivity = 0, Protective Equipment = B (Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

Unisource Worldwide, Inc.		LEPHONE NUMBER		TION: 1-770-4	47-9000	
6600 Governors Lake Parkway		TE PRINTED: Augus			47 0000	
Norcross, GA 30071	NAME OF PREPARER: Regulatory Compliance					
www.unisourcelink.com						
SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION						
Chemical Names	CAS#	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.	
Mineral Spirits	64742-48-9	NO	177 ppm*/NE	177 ppm*/NE	1-5	
Synthtic Isoparaffinic Hydrocarbon	64742-47-8	No	NE / NE	177 ppm*/NE	1-5	
Liquefied Petroleum Gas Mixture	See below	No	/	/	30 – 40	
Propane	74-98-6		1000 ppm/NE	1000 ppm/NE		
n-Butane	106-97-8		1000 ppm/NE	NE/NE		
	<u> </u>					
Balance of ingredients are non-hazardous or below reportable levels. * ExxonMobil recommendation						
SECTION III - PHYSICAL CHARACTERISTICS						
Boiling Point: NA Vapor Pressure (psig): 96 @ 130F / 48 @ 70F Specific Gravity (H20=1): 0.7900 pH: 6-						
8						
Solubility/Water: Moderate Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND						
Appearance and Odor: Aerosol spray with fragrant odor.						
SECTION IV - FIRE AND EXPLOSION HAZARD DATA						
Aerosol Flammability: Product does not need to be labeled as flammable as described in 40 CFR 156.10. Flashpoint: <0F (Propellant); >120F (Concentrate) Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5 Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical. Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up. Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers. Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.						
SECTION V - REACTIVITY DATA						
Stability: Stable Hazardous Polymerization: NA   Incompatibility (Materials to Avoid): Strong oxidizing agents. Hazardous Decomposition Products:   Carbon monoxide and hydrocarbon gases may be formed. Conditions to Avoid: Keep away from heat, sparks and flames. Dropping of containers may cause bursting.						
	SECTION VI -	HEALTH HAZARD D				
Route(s) of Entry - Inhalation HAZARDS IDENTIFICATION: E cause irritation. INHALATION: Prolonged exposure high concentrations. INHALATION: Asp development and	YES: May cause e can be irritating	mild irritation. SKIN: F to eyes, nose and res	piratory tract. C	an be harmful o	-	



duration. Unconsciousness is immediate in sudden acute asphyxia. Slow development may cause rapid breathing, dizziness, incoordination, fatigue, and progress to nausea, vomiting, and possibly death. INGESTION: May be harmful if swallowed. Possible aspiration hazard. May cause inflammation of the lungs. AGGRAVATED MEDICAL CONDITIONS: May aggravate pre-existing skin conditions.

CHRONIC EFFECTS/TARGET ORGANS: None known.

EMERGENCY AND FIRST AID PROCEDURES: EYES: Immediately flush with plenty of water for at least 15 minutes. Get prompt medical attention. SKIN: Wash with soap and plenty of water. INHALATION: Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration. INGESTION: Get immediate medical attention. Do NOT induce vomiting unless directed by medical personnel. Never give anything by mouth to an unconscious person.

CARCINOGENICITY: No regulated ingredients.

TOXICITY INFORMATION: No data available.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Releases or Spills: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material.

Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.

Handling And Storing: Avoid breathing vapor. Keep away from heat, sparks and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 120F (48.9C). Store as Level 1 Aerosol (NFPA 30B).

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

### SECTION VIII - EMPLOYEE PROTECTION

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceeds occupational

exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.

Ventilation: General ventilation is adequate under normal conditions; mechanical ventilation is optional. Protective Gloves: Chemical resistant gloves are recommended – consult glove manufacturer to determine the proper type for a specific operation.

Eye Protection: Safety glasses are recommended.

Other Protective Clothing or Equipment: Wear impervious clothing to prevent skin contact.

Work/Hygienic Practices: Ensure strict sanitary conditions are conformed to when working around chemicals. Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

### SECTION IX - OTHER REGULATORY CONTROLS

FEDERAL:

Toxic Substance Control Act (TSCA): Ingredients of this product are listed on the EPA/TSCA Inventory of Chemical

Substances.

USEPA: Registration Number 706-83

STATE RIGHT-TO-KNOW:

Pennsylvania/New Jersey Right-To-Know (Chemical and CAS No.):

	,
Deionized water	7732-18-5
Mineral spirits	64742-48-9

Mineral spirits 64742-48-9 Synthetic isoparaffinic hydrocarbon 64742-47-8

Liquefied Petroleum Gas Mixture See below

Propane 74-98-6

n-Butane 106-97-8

## SECTION X - TRANSPORTATION REQUIREMENTS (D.O.T. CLASSIFICATION)

Shipping Name: Consumer CommodityHazard Class: ORM-DNG-- NegligibleNA-- Not ApplicableNE-- Not EstablishedUN-- UnavailableND-- Not DeterminedWhile the information set forth herein is believed to be accurate as of the date hereof, the Company makes no<br/>warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.EFFECTIVE DATE:8/29/05SUPERCEDES:8/9/01PREPARED BY: Regulatory Compliance