



MATERIAL SAFETY DATA SHEET

24 HOUR EMERGENCY PHONE

CHEMTREC 1-800-424-9300

2470 Warren Avenue

Twin Falls, Idaho 83301

☎ (208)734-7279 ♦ 1-800-367-3250

FAX (208)733-0460

PRODUCT
1057

SECTION 1: PRODUCT IDENTIFICATION

TRADE NAME: 1057
CHEMICAL NAME: Proprietary
CHEMICAL FAMILY: Alkyl Alkanol Amine
FORMULA: Proprietary
CAS NUMBER: Mixture
EPA TSCA INVENTORY: None of the ingredients of this product are listed in the Inventory Of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under authority of the Toxic Substances Control Act (TSCA).

DOT PROPER SHIPPING NAME: Corrosive liquid, n.o.s.
DOT HAZARD CLASS: Corrosive Material
DOT I.D. NUMBER: UN 1760
DOT LABEL(S): Corrosive
RQ PER EPA CERCLA REGS: Not Listed
EPA RCRA HAZ WASTE NO.: D002

SECTION 2: HAZARDOUS INGREDIENTS

ONE PERCENT OR GREATER NAME: Diethylaminoethanol
CAS NUMBER: 100-37-8
PERCENT: 1 to 15
TLV: 10 ppm, 50 mg/m³
CARCINOGEN 0.1 PERCENT OR GREATER: None

SECTION 3: PHYSICAL DATA

SPECIFIC GRAVITY: 0.980 to 1.000
pH: 11.00 to 11.60
FLASH POINT (For 99.5% active): 125° F
BOILING POINT (For 99.5% active): 316-326° F
VAPOR PRESSURE (mm/Hg): 1.4 HG @ 20° C (For 99.5% active)
% VOLATILE BY VOLUME (For 99.5% active): 100%
VAPOR DENSITY (Air = 1) (For 99.5% active): 4.0
EVAPORATION RATE (=1): N/E
SOLUBILITY IN WATER: Complete
REACTIVITY IN WATER: No
APPEARANCE AND ODOR: Water white color with amine odor
FLAMMABLE LIMITS IN AIR % BY VOLUME: LOWER: 6.7% UPPER: 11.7% (For 99.5% active)
AUTO-IGNITION TEMPERATURE: N/E

MATERIAL SAFETY DATA SHEET
1057

SECTION 4: FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA: Dry Chemical, CO₂, Halon, Water Spray or Standard Foam
UNUSUAL FIRE AND EXPLOSION HAZARD: May be ignited by excessive heat or flames. Container may explode in fire. Fire may cause irritating or poisonous gases.
THERMAL DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides

SECTION 5: HEALTH HAZARDS

ACGIH THRESHOLD LIMIT VALUE (TLV): TWA – 10 ppm; 50 mg/m³
OSHA PERMISSIBLE EXPOSURE LIMIT (PEL): TWA – 10 ppm; 50 mg/m³
PRIMARY ROUTE(S) OF ENTRY: Inhalation, Skin
TOXICITY DATA: Oral: Rat LD₅₀ 1300 mg/kg
Dermal: Rabbit LD₅₀ 1100 mg/kg
Inhalation: Mouse LC₅₀ 5000 mg/m³ (1000 ppm)

NFPA HAZARD RATING
(0-1-2-3-4, 0=LEAST/4=MOST): Health 2 Flammability 2 Reactivity 0
SIGNS AND SYMPTOMS OF EXPOSURE: 1. ACUTE OVER EXPOSURE
May cause burns to skin and eyes and respiratory irritation.
2. CHRONIC OVER EXPOSURE
Prolonged exposure may cause dermatitis

MEDICAL CONDITIONS GENERALLY
AGGRAVATED BY EXPOSURE: Skin and Respiratory conditions.
CHEMICAL(S) LISTED AS CARCINOGEN
OR POTENTIAL CARC. BY NATIONAL
TOXICOLOGY PROGRAM: None
I.A.R.C. MONOGRAPHS: None
OSHA: None

EMERGENCY AND FIRST AID PROCEDURES: 1. INHALATION: Remove to fresh air; if not breathing, give artificial respiration; if breathing is difficult, give oxygen.
Seek medical attention.
2. EYES: Flush with plenty of water for at least fifteen minutes and seek medical attention immediately.
3. SKIN: Flush with water while removing contaminated clothing. Continue washing after clothing is removed. Wash contaminated clothing before reuse. Destroy contaminated shoes.
4. INGESTION: Do not induce vomiting. Drink water or milk to dilute and seek medical attention.

SECTION 6: REACTIVITY DATA

STABILITY: Stable
CONDITIONS TO AVOID: Strong Acids; Strong Oxidizers
HAZARDOUS DECOMPOSITION PRODUCTS: See Thermal Decomposition
HAZARDOUS POLYMERIZATION: Will not occur
CONDITIONS TO AVOID: Heat, Flames, Sparks, Acids, Oxidizers

SECTION 7: SPILL OR LEAK PROCEDURES

PROCEDURE FOR LARGE SPILL/RELEASE: Dike far ahead of liquid spill for later disposal. Pump into approved recovery containers for disposal. Keep out of watersheds and waterways.
PROCEDURE FOR SMALL SPILL/RELEASE: Do not touch spilled material. Stop leak if you can do it without risk. Take up with sand or other noncombustible, absorbent material and place into containers for later disposal.
WASTE DISPOSAL: Dispose of in accordance with all applicable federal, state, and local laws or ordinances and regulations governing handling, transportation and disposal of hazardous waste materials and environmental protection.

SECTION 8: SPECIAL PROTECTION

RESPIRATORY: Use an approved respirator suitable for ammonia vapor.
VENTILATION: Provide ventilation that will keep airborne contaminants within prescribed limits.
PROTECTIVE EQUIPMENT: Chemical goggles or face shield and rubber gloves. Other protection for skin and clothing is recommended.

MATERIAL SAFETY DATA SHEET
1057

SECTION 9: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Material is a hazardous waste due to corrosivity.
Store away from open flame or extreme heat.

OTHER PRECAUTIONS: Avoid breathing vapors or skin contact.

SECTION 10: MISCELLANEOUS

WATERTECH, Inc. has compiled the information contained in this MATERIAL SAFETY DATA SHEET from sources believed to be reliable and to represent current opinion on the subject when the MSDS was prepared. No warranty, guarantee or representation is made as to the correctness or sufficiency of the information. The user of this product must determine for themselves what safety measures are necessary to safely use this product, either alone or in combination with other products.