## LASER CHEM'S AMAZING TAR & GREASE REMOVER

Material Safety Data Sheet 公共 医医皮 医医性 医多种 医医性 医耳耳耳耳 计可以 医皮肤 医内耳耳 医耳耳 经 医 医 医 医 医 医 医 医 医 医 SECTION I - PRODUCT IDENTIFIER Product: Laser Chem's Amazing Tar & Grease Remover Supplier: Laser Chem Int. Corp. 7022 South 400 West Midvale, UT 84047 1-800-272-2741 EMERGENCY TELEPHONE: 1-800-535-5053 NFPA Ratings: /Health: 1 /First 2 /React: 0 /Special:- /0=LEAST TO 4=EXTREME HMIS PERSONAL PROT: B SECTION II - HAZARDOUS INGREDIENTS Hazardona Components-(CAS Number) Exposure Limits Propylene glycol n-butyl ether (5131-66-8)........No Data Established
Dipropylene glycol methyl ether (34590-94-8)......OSHA TWA (skin) 100 ppm, STEL 150 ppm.ACGIH TLV(skin)100 ppm, STEL 150ppm Ethyl alcohol (64-17-5) -----OSHA TWA 1000 ppm, ACGIH TWA 1000 ppm SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS Melting Point: NA Boiling Point: 350-400 deg. F Specific Gravity (H20=1): 548 Vapor Pressure: <3 mmHg @ 20 deg. C Vapor Density (Air=1): ND Evaporation Rate (BuAc=1): <1 VOC: 180 gm/L pH: ND Solubility in Water: Appreciable Appearance and Odor: Clear liquid solution with an acatate odor. SECTION IV - FIRE AND EXPLOSION HAZARD DATA Flash Point (Method): Approx. 127 deg. F (TCC) Flammable Limits: Lower [ 1.8 ] Upper [ 19 ] Extinguishing Media: Dry powder, carbon dioxide (CO2), "alcohol" foam, use water to cool containers. Special Fire Fighting Procedures: Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors, on the downwind side. Firefighters wear protective clothing, and self contained breathing apparatus. Unusual Fire and Explosion Hazards: If stored in drums: Containers may repture from internal pressure if confined to fire area. Cool with water. Get non-emergency personnel out of the area. SECTION V - REACTIVITY INFORMATION Stability: Product is Stable Materials to Avoid: Oxidizers or oxidizing materials. Alkaline materials. Strong acids. Hazardous Decemposition or Byproducts: From combustion: Smoke, Carbon monoxide, carbon dioxide. Hazardons Polymerization: Will not occur. SECTION VI - HEALTH HAZARD DATA Routes of Entry Skin/Eyes? yes - irritani Inhelation? possible - irritant, narcotic poesible-irritant, marcotic Ingestion? Skin Absorption? not likely Health Hazards Acute: Inhalation of vapors may be narcotic or anesthetic. Ingestion of liquid will cause gastrointestinal distress, irritation, and possibly names. Liquid or vapors may be irritating to skin and eyes. Chronic Unknown OSHA Regulated? NO NO IARC Monographs? Carcinogenicity: Listed in NTP? NO Signs and Symptoms of Exposure: Skin irritation develops slowly after contact, eye irritation develops immediately upon contact. Prolonged exposure can cause: Nausea, headache, vomiting and narcotic effects (Dizziness, confusion, etc.). Medical Conditions Generally Aggravated by Exposure: Pre-existing skin disorders.

## LASER CHEM'S AMAZING TAR AND GREASE REMOVER

FIRST AID REOCEDURES

Eye Contact: Flush eyes with water 15 minutes. Get medical attention if symptoms develop and persist.

Skin Contact: Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek medical attention if symptoms develop and persist.

Ingestion: Do NOT Induce vomiting, get medical atlention.

Inhalation: Remove victim to fresh air and, if needed, immediately begin artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. Contact a physician immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spill or Leak Procedures: Emergency response coordinator must have mandated training. Small spills, pick up with absorbent media. Store as INDUSTRIAL waste. Large spills, contain with dikes, pick up with vacuum truck. Handle as INDUSTRIAL waste. Notify proper local, state, and federal authorities.

Precautions to be Taken in Handling and Storage: Store in a cool, oxidizers or materials bearing a yellow "D.O.T." label. Store away

ventilated area, away from ignition sources. Store away from from alkaline materials. Store away from acids.

Other Precautions: Clean up leaks/spills immediately to prevent

soll or water contamination.

Respiratory Protections: Not normally needed under proper

conditions of use and storage.

Ventilation: Local Exhaust - Recommended

Special - Not

necessary, Mechanical - Recommended Other - Not necessary

Protective Gloves: Chamical impervious gloves.

Eye Protection: Chemical goggles or full face shield.

Other Protective Equipment: Boots, aprom, drench showers, eye wash as needed for protections against spills and/or splashes.

Work Hygienic Practices: Avoid contact with skin, eyes, and clothing. After handling this product, wash hands before eating drinking or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown in section VI. Launder contaminated clothing before reuse.

SECTION IX - TRANSPORTATION INFORMATION

Domestic: In containers greater than 110 gallons bulk Combustable liquid, n.e.s., Combustable Liquid, NAI993, PGIIL in continners less than 110 gallons bulk, Amazing, not regulated.

SECTION X - REGULATORY/ENVIRONMENTAL

EPA Hazards: Acute-Yes Chronic-No Flammability-Yes
Sudden Release of Pressure-No Reactive-No

SARA Title III - Section 313, Toxic Materials: NONE Clean Air Act: section 111. Clean Water Act: Not listed

States Lists: Massachusetts, Pennsylvania, New Jersey

Toxic Substances Control Act (TSCA), 40 CFR 710 Sources of the raw materials used in this mixture assure that all chemical ingredients present are in compliance with Sect. 8(b) Chemical Substance Inventory, or are otherwise in compliance with TSCA.

Pootnotes:

NA-Not applicable NE-Data not established CS-Cancer Suspect Agent OX-Oxidizer ND-No data

Cor-Corrosive CALC-Calculated EST-Estimated STEL-Short Time Exposure Limit

TLV-Threshold Limit Value PEL-Permissible Exposure Limit TWA-Time Weighted Average, 8 hours

HMIS, PPI-Hazardous material Identification System, personal Protection Index

The data presented is true and correct to the best of our knowledge and belief, however, neither seller nor preparer makes and warranties, express or implied, concerning the information presented. The user is cantioned to perform his own hazard evaluation and to rely upon his own determination.

Form essentially the same as OSHA Form 174 dated September 1985.

Prepared 4/24/95