### Quote Specification Vendor: SCHETKY NW SALES

THOMAS BUILT BUS

**PART I** 

TYPE D—84 PASSENGER, REAR ENGINE
Use this document to bid both non-lift and lift buses for 61 – 84 capacity

ITEM	SPECIFICATIONS  Vendor must meet or exceed these specifications.  Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Seating Capacity	84 passenger maximum design capacity seated for 78 passenger.	Capacity w/o lift 78  Capacity w/lift N/A		
Alternator	240 amp minimum. Lift-equipped or air-conditioned. Manufacturer recommended capacity.	Mfr. <u>LEECE-NEVILLE</u> Amps output w/o lift or A.C. <u>240</u> Amps output w/lift or A.C. N/A		
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. BERGSTROM		
Axle—Front	13,200 lb. minimum total suspension GVWR.	Mfr. DETROIT Capacity13,200-LB		
Axle—Rear	23,000 lb. minimum total suspension GVWR.	Mfr. DETROIT 23,000-LB Capacity		
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. CR		
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Ratio <u>5.57</u>		
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round: ☐ Diameter Other: ☒ Square inches 22		
Battery(ies)	1400 CCA 12 volt to be mounted in body battery compartment.	Number of batteries 2 CCA 1900		
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	☐ Swing out ☐ Roll out		
Brakes	Air: Drum or Disc. If Drum, minimum 16.5" x 6" front, minimum 16.5" x 8" rear. Refer to Washington State School Bus Specifications Manual.	Disc         Front         □         Rear         □           Drum         Front         ☒         Rear         ☒           Size         16.5X6         Rear         16.5X8 5/8		
Door, Service	Power operated.	<ul> <li>☐ Folding</li> <li>☐ Other</li> <li>☐ Roll out</li> <li>☑ Split, Outward opening</li> </ul>		
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Mfr. NATIONAL		

# TYPE D—84 PASSENGER, REAR ENGINE Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I (cont.) Vendor: <u>SCHETKY NW SALES</u> **THOMAS BUILT BUS** 

ITEM	SPECIFICATIONS  Vendor must meet or exceed these specifications.  Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Engine	Diesel—280 H.P. minimum, located in the rear.			R.P.M R.P.M
Engine Heater	Engine manufacturers recommended in-block heater.	Watts <u>750</u> Volts <u>12</u> Mfr. PHILLIPS		
Engine Temperature	To be controlled electronically, by fan clutch/drive, or shutters.	Mfr. <u>EATON</u> ☐ Electronic ☐ Fan clutch ☐ Shutters		
Fuel Tank	100 gallon minimum.	Capacity 100 GALLON		
Heaters	Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors. Must include recirculating pump.	Front B.T.U. <u>90.000</u> Center B.T.U. <u>50,000</u> Rear B.T.U. <u>50,000</u> Total B.T.U. <u>190,000</u>		
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights–7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified ⊠  If not, explain.		
P.A. System	AM/FM/PA radio with 4 interior and 1 exterior speakers.	Mfr. <u>DELPHI</u> Model No. <u>DEA700</u>		
Seat Spacing	78 passenger based upon manufacturer's maximum seat spacing.	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: 396.5 inches  Mfg.'s C/C seat measurement: 30 inches		
Steering Wheel	Tilt and telescoping column.	Check if as specified ⊠		
Step Tread	Studded or pebbled top tread covering.	Mfr. KOROSEAL		
Tires	6 first quality, radial ply. No low profile tires.	Mfr. HANKOOK Size 11R22.5 Load range H		

## State Price Quote Specification TYPE D—84 PASSENGER, REAR ENGINE

THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61 - 84 capacity

ITEM	SPECIFICATIONS  Vendor must meet or exceed these specifications.  Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) <u>6.9</u>	
Transmission	Automatic—Allison, PTS 3000 or equal.	Mfr. ALLISON	
		Model no. 3000PTS	
		Net input torque 660	
		Net input H.P. 280	
Two-way	45-watt, VHF, mil. spec.	Mfr. MOTOROLA	
Communications		Model No. CM300D	
Wheels	6 to be compatible with tire size.	Size <u>22.5"</u>	
		Rim width 8.25"	
	SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY		
Wheelchair Lift—	Must meet state specification. Platform shall be a minimum of 32" x	Mfr. N/A	
Installed	52".	Model No	
Wheelchair/	Must meet state specification.	Mfr	
Occupant Tie- down System— Installed		Model No	

# TYPE D—84 PASSENGER, REAR ENGINE Use this document to bid both non-lift and lift buses for 61 – 84 capacity

**Vendor: SCHETKY NW SALES** THOMAS BUILT BUS

ITEM	Item	SPECIFICATIONS must meet or exceed these specifications. bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
	ADDITIONAL	REQUIREMENTS—CHASSIS AND BODY	
Line Setting Ticket		nufacturer's Line Setting Ticket will be delivered packet at the time of delivery of the bus.	Check if as specified ⊠
Owner's/Operator's Handbook		assis manufacturer's owner's/operator's handbook urnished with each bus at time of delivery.	Check if as specified ⊠
Repair Manuals	manuals, including	chassis, engine, transmission, and body repair wiring diagram for all components, will be made delivery, with instructions available on accessing	Check if as specified ⊠
Service and Cleaning	<ul> <li>Chassis lubric</li> <li>Check fluid le</li> <li>Cooling syste</li> <li>Interior and ex</li> <li>All systems (exinspected to exinspected)</li> </ul>	vels: verify all are at recommended full levels. m protected at -20°F. kterior will be clean (including glass). lectric, air, hydraulic, mechanical, and manual) be ensure proper operation at time of delivery. ts and accessories will be installed and operational	Check if as specified ⊠
Warranty	A complete copy of delivery.	f all warranty agreements will be furnished at time	Check if as specified ⊠



STUDENT TRANSPORTATION Old Capitol Building PO BOX 47200 Olympia, WA 98504-7200 (360) 725-6120 TTY (360) 664-3631

#### VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION TYPE D—84 PASSENGER, REAR ENGINE

		-
VENDOR'S COMPANY NAME SCHETKY NW SALES INC	REPRESENTATIVE'S NAME SCOTT MEYER	TELEPHONE NUMBER 509-579-6267
ADDRESS 8430 NE LOMBARD ST PORTLAND, OR 97220	Estimated delivery date to school district fr Firm where engine and chassis can be set  SCHETKY  Firm where body can be serviced or repair	

BODY					
MAKE THOMAS		Warranty: Years <u>1</u> Miles UNLIM	Inside measurement from rear of stepwell to appropriate point at	Equipped seating capacity: w/o lift 78 w/lift N/A	
MODEL 370DS	YEAR 2025	Seat color: <u>GRAY</u> Floor color: <u>BLACK</u>	rear of passenger seating area: w/o lift 396.5 w/lift N/A	Overall vehicle length (inches): w/o lift 469.9 w/lift N/A	

	CHASSIS		EN	IGINE
MAKE THOMAS		Warranty: Years <u>1</u> Miles <u>UNLIM</u>	MANUFACTURER CUMMINS	Torque: <u>660</u> @ <u>1600</u> RPM H.P.: <u>280</u> @ <u>2400</u> RPM
MODEL 370DS	YEAR 2025	Wheelbase: 267	MODEL YEAR 2025	C.I.D. : <u>6.7L</u> Fuel type : <u>DIESEL</u>
	TRANSMISSION		Warranty: Years <u>5</u>	Battery type/grp: <u>31</u>
MANUFACTURER ALLISON		Speeds forward: 5	Miles <u>100,000</u>	Number batteries: 2
MODEL 3000PTS		Warranty: Years <u>5</u> Miles <u>UNLIM</u>	Number of cylinders: <u>6</u> Inline <u>X</u> V-type	_Total CCA: <u>1900</u>

QUOTEI	O PRICE			
Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).				
	Bid—w/lift \$ NO BID			
Scott Meyer	08/06/2024			
	,			

PART II

#### **State Price Quote Specification**

### **DISTRICT-SUPPORTED OPTIONS**

□C60	□C77	□ <b>D60</b>	<b>⊠D84</b>
------	------	--------------	-------------

PARTII
Vendor: <u>SCHETKY NW</u>
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications.  Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
Activity	2-passenger position seats with lap-shoulder belts in all passenger	Passenger Capacity 52		
Securement Seating	positions.	Cost \$ <u>650.00 PER SEAT, R</u>	EPLACE STD SEAT	
	To cool passenger compartment as required in the Washington State	Mfr. CARRIER 104K BTU		
Air Conditioning	School Bus Specifications manual.	Cost \$ 17,250.00		
Alternate Fuel	Must comply with power and gradeability formula. Refer to	Mfr. <u>N/A</u>		
	Washington State School Bus Specifications manual. Must comply with	□ Cost \$		
☐ Electric	all the requirements of FMVSS No. 305.	☐ Electric Cost \$		
		Cost \$ <u>1,650.00</u>	Capacity <u>270AMP</u>	
Alternator	Available options.	Cost \$ 2,225.00	Capacity <u>320AMP</u>	
		Cost \$	Capacity	
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ 195.00		
Anti-spray Device	Rubbei leiluei exteriueis.	Type D: Cost \$ 375.00		
Back-up Alarm	Must meet state specification.	Mfr. THOMAS		
back-up Alaim	Must meet state specification.	Cost \$ 175.00		
Brakes	4-wheel hydraulic disk brake.	Cost \$ N/A Deduct \$ N/A		
	Air, Drum or Disc. Refer to Washington State School Bus	Disc Cost \$ 4,350.00	Disc Deduct \$ N/A	
Brakes	Specifications manual.	Drum Cost \$ INCLUDED	Drum Deduct \$ N/A	
Color	Exterior white roof.	Cost \$ 790.00		
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>350.00</u>		
		Non-Air	Air	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth	Mfr. N/A	Mfr. NATIONAL	
	panel covers.	Cost \$ INCLUDED	Cost \$ INCLUDED	
Fire Suppression	Jomarr VT-6-E-NAF, or equal engine compartment fire suppression	Mfr. FOGMAKER		
System	system of appropriate size to be installed according to manufacturer recommendation.	Cost \$ 6,300.00		
Floor Color	Nonstandard color.	Cost \$ 950.00		

# State Price Quote Specification DISTRICT-SUPPORTED OPTIONS

□C60	□C77	□ <b>D60</b>	<b>⊠D84</b>
------	------	--------------	-------------

PART II (cont.)
Vendor: SCHETKY NW
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Fuel Tank	Larger fuel capacity (Diesel only).	Size: <u>INCLUDED</u>	Cost \$
Fuel Tank	Larger fuel capacity (Propane only).	Size: N/A	Cost \$
Headlights	Halogen.	Cost \$ INCLUDED	
Headlights	L.E.D.	Cost \$ 950.00	
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>WEBASTO</u> Cost \$ 5,500.00	Model: PRO90
Noise Reduction	Exceeding minimum specifications.	Driver compartment Engine compartment Full acoustical headliner	Cost \$ <u>250.00</u> Cost \$ <u>INCLUDED</u> Cost \$ <u>990.00</u>
Retarder	Manufacturer's standard.	Driveline □ Exhaust ⊠ Transmission □	Cost \$ Cost \$ <u>175.00</u> Cost \$
Seat Belt Ready Seat	3-passenger position seat with securement belts.	Cost \$ 1,225.00	
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ 12,718.00 Capacity 44 3 by 2 Cost \$ 12,718.00 Capacity 44 3 by 3 Cost \$ 16,184.00 Capacity 84	

## **DISTRICT-SUPPORTED OPTIONS**

<b>□C60</b>	□C77	□ <b>D60</b>	<b>⊠D84</b>
-------------	------	--------------	-------------

PART II (cont.)
Vendor: <u>SCHETKY NW</u>
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.		
	Item bid shall be specified in column to right.	Left side 21.4		
		Cost \$ <u>1,375.00</u>		
Storage	Largest available for unit bid.		cubic feet.	
Compartments		Cost \$ <u>1,375.00</u>		
			cubic feet.	
		Cost \$ <u>5,600.00</u>		
		Mfr. <u>THOMAS</u>	Mfr. THOMAS	
Strobe Light	Exterior roof mounted white strobe light.	Model No. <u>DOUBLE FLASH</u>		
		Cost \$ 295.00		
0		Mfr. THOMAS		
Student Protection System—Installed	Electronic system to insure driver post-trip inspection of passenger compartment.	Model No. PASS-ADVISORY		
System—installed		Cost \$ 390.00		
Suspension	Air ride (Air brake system only).	Front	Rear	
Suspension		Cost \$ N/A	Cost \$ 4,025.00	
Toolbox	Interior, manufacturer standard.	Cost \$ 85.00 Deduct \$ N/A		
T ( D :	Automatic chains.	Mfr. ON-SPOT		
Traction Device		Cost \$ 4,950.00		
<b>- -</b> .	Sanders.	Capacity 158LB		
Traction Device		Cost \$ <u>6,100.00</u>		
	Automatic—Allison, PTS 3000 or equal.	Mfr. INCLUDED		
Transmission		Model No.		
		Cost \$		
Vehicle		<del>-</del>		
Securement System	Must meet state specification.	Mfr. <u>SAFETY BRAKE</u>	Cost \$ <u>2,150.00</u>	

# State Price Quote Specification DISTRICT-SUPPORTED OPTIONS

<b>□C60</b>	□C77	□ <b>D60</b>	<b>⊠D84</b>
-------------	------	--------------	-------------

PART II (cont.)
Vendor: SCHETKY NW
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID  Price of items bid will establish the district cost.	
Video Camera	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Mfr. SEON	
Systems—		Model No. <u>DH</u>	
Installed		Cost \$ <u>4,230.00</u> H	low many cameras <u>3</u>
	Must meet state specification.	Stand Alone System	Added to Interior System
Video Camera		Mfr. <u>SEON</u>	Mfr. SEON
Systems—Stop Sign Camera— Installed		Model No. <u>DH</u>	_ Model No. <u>DH</u>
		Cost \$ 4,780.00	Cost \$ 705.00
		How many cameras <u>4</u>	How many cameras <u>1</u>
Warning Light	16 light monitoring system.	Incandescent	LED Lights
Monitor		Cost \$ N/A	Cost \$ 750.00
Additional	Must meet state specification.	Mfr. N/A	
Wheelchair/Occup ant Tie-down		Model No	
System—Installed		Cost per station \$	
,	Laminated passenger-compartment side or rear glass.	Side Cost \$ <u>1,500.00</u>	
Windows		Rear Cost \$ INCLUDED INSIDE COST	
		Both Cost \$ <u>1,500.00</u>	
Windows	Tinted.	Cost \$ 750.00	
Windows	Thermal pane, left of driver and service door.	Cost \$ 895.00	