

State Price Quote Specification
**TYPE D—84 PASSENGER
ELECTRIC**

PART I

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61 – 84 capacity

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Seating Capacity	84 passenger maximum design capacity seated for 78 passengers.	Capacity w/o lift <u>78</u> Capacity w/lift <u>N/A</u>
Auxiliary Fans	2 fans, 6" maximum, mounted to right and left windshield and service door.	Mfr. <u>BERGSTROM</u>
Axle—Front	13,200 lb. minimum total suspension GVWR.	Mfr. <u>DETROIT</u> Capacity <u>13,200-LB</u>
Axle—Rear	23,000 lb. minimum total suspension GVWR.	Mfr. <u>DETROIT</u> Capacity <u>23,000-LB</u>
Axle Oil Seals	Front and rear oil bath, or maintenance free sealed greased bearings.	Mfr. <u>CR</u>
Axle Ratio	Must comply with power and gradeability formula. Refer to Washington State School Bus Specifications Manual.	Ratio <u>6.14</u>
Back-up Lights	All required backup lights to be LED (Light Emitting Diode). Refer to Washington State School Bus Specification's Manual.	Round: ☐ Diameter _____ Other: ☒ Square inches <u>22</u>
Battery(ies)	1400 CCA 12 volt to be mounted in body battery compartment.	Number of batteries <u>2</u> CCA <u>1900</u>
Battery(ies) Propulsion	Battery propulsion must meet a minimum of 130 kWh.	Number of batteries <u>1</u> kWh <u>244</u>
Battery Compartment	Battery storage tray must be large enough to accommodate batteries as specified in chassis section.	☐ Swing out ☒ Roll out
Brakes	Air: Drum or Disc. If Drum, minimum 16.5" x 6" front, minimum 16.5" x 8" rear. Refer to Washington State School Bus Specifications Manual.	Disc Front ☐ Rear ☐ Drum Front ☒ Rear ☒ Size Front <u>16.5X6</u> Rear <u>16.5X8 5/8</u>
Door, Service	Power operated.	☐ Folding ☐ Other ☐ Roll out ☒ Split, Outward opening

State Price Quote Specification
TYPE D—84 PASSENGER
ELECTRIC

Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I (cont.)

Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

ITEM	SPECIFICATIONS Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Mfr. <u>NATIONAL</u>
Motor	190 H.P. minimum, located in the rear.	Engine mfr. <u>PROTERRA</u> Model or liters <u>PRO-DRIVE</u> Net torque <u>1200</u> @ _____ R.P.M Net H.P. <u>295</u> @ _____ R.P.M
Heaters	Heaters Minimum of 3 heaters; 1 front, 1 center, 1 rear. Shutoff valves at engine for all heaters. Two-speed motors.	Front B.T.U. <u>90,000</u> Center B.T.U. <u>50,000</u> Rear B.T.U. <u>50,000</u> Total B.T.U. <u>190,000</u>
Lights	LED (Light Emitting Diode). Includes Clearance Lights, Stop Lights—7", Taillights, Turn Signals, Eight-Light System, and Dome-Light System.	Check if as specified ☒ If not, explain. _____
P.A. System	AM/FM/PA radio with 4 interior and 1 exterior speakers.	Mfr. <u>DELPHI</u> Model No. <u>DEA700</u>
Seat Spacing	78 passengers based upon manufacturer's maximum seat spacing.	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: <u>406.5</u> inches Mfg.'s C/C seat measurement: <u>30</u> inches
Steering Wheel	Tilt and telescoping column.	Check if as specified ☒
Step Tread	Studded or pebbled top tread covering.	Mfr. <u>KOROSEAL</u>
Tires	6 first quality, radial ply. No low-profile tires.	Mfr. <u>HANKOOK</u> Size <u>11R22.5</u> Load range <u>H</u>

State Price Quote Specification
**TYPE D—84 PASSENGER
ELECTRIC**

PART I (cont.)
Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

Use this document to bid both non-lift and lift buses for 61 – 84 capacity

ITEM	SPECIFICATIONS	VENDOR SPECIFICALLY IDENTIFY ITEM BID
	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	Price of items bid will establish the district cost.
Toolbox	Exterior, manufacturer standard.	Size (cubic feet) <u>6.9</u>
Two-way Communications	45-watt, VHF, mil. spec.	Mfr. <u>MOTOROLA</u>
		Model No. <u>CM300D</u>
Wheels	6 to be compatible with tire size.	Size <u>22.5"</u>
		Rim width <u>8.25"</u>
	SPECIAL NEEDS REQUIREMENTS—CHASSIS AND BODY	
Wheelchair Lift—Installed	Must meet state specification. Platform shall be a minimum of 32" x 52".	Mfr. <u>N/A</u>
		Model No. _____
Wheelchair/ Occupant Tie-down System—Installed	Must meet state specification.	Mfr. _____
		Model No. _____

State Price Quote Specification
**TYPE D—84 PASSENGER
ELECTRIC**

Use this document to bid both non-lift and lift buses for 61 – 84 capacity

PART I (cont.)
Vendor: SCHETKY NW SALES
THOMAS BUILT BUS

ITEM	SPECIFICATIONS	VENDOR SPECIFICALLY IDENTIFY ITEM BID
	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	Price of items bid will establish the district cost.
	ADDITIONAL REQUIREMENTS—CHASSIS AND BODY	
Line Setting Ticket	Legible copy of manufacturer's Line Setting Ticket will be delivered with each vendor's packet at the time of delivery of the bus.	Check if as specified ☒
Owner's/Operator's Handbook	One copy of the chassis manufacturer's owner's/operator's handbook or manual will be furnished with each bus at time of delivery.	Check if as specified ☒
Repair Manuals	A complete set of chassis, engine, transmission, and body repair manuals, including wiring diagram for all components, will be made available at time of delivery, with instructions available on accessing repair materials.	Check if as specified ☒
Service and Cleaning	Cleaning and service by vendor prior to delivery will include: • Chassis lubrication. • Check fluid levels: verify all are at recommended full levels. • Cooling system protected at -20°F. • Interior and exterior will be clean (including glass). • All systems (electric, air, hydraulic, mechanical and manual) be inspected to ensure proper operation at time of delivery. • All components and accessories will be installed and operational at time of delivery.	Check if as specified ☒
Warranty	A complete copy of all warranty agreements will be furnished at time of delivery.	Check if as specified ☒



Washington Office of Superintendent of
PUBLIC INSTRUCTION
2024-2025

STUDENT TRANSPORTATION
Old Capitol Building
PO BOX 47200
Olympia, WA 98504-7200
(360) 725-6120 TTY (360) 664-3631

VEHICLE DATA SHEET AND OFFICIAL PRICE QUOTATION TYPE D—84 PASSENGER—ELECTRIC

VENDOR'S COMPANY NAME SCHETKY NW BUS SALES INC		REPRESENTATIVE'S NAME SCOTT MEYER	TELEPHONE NUMBER 509-579-6267
ADDRESS 8430 NE LOMBARD ST. PORTLAND, OR 97220		Estimated delivery date to school district from time purchase order is received: <u>260-280</u> Firm where engine and chassis can be serviced or repaired, and parts obtained: <u>SCHETKY</u> Firm where body can be serviced or repaired, and parts obtained: <u>SCHETKY</u>	

BODY

MAKE THOMAS BUILT BUS	Warranty: Years <u>1</u> Miles <u>UNLIM</u>	Inside measurement from rear of stepwell to appropriate point at rear of passenger seating area: w/o lift <u>406.5</u> w/lift <u>N/A</u>	Equipped seating capacity: w/o lift <u>78</u> w/lift <u>N/A</u>
MODEL 380DS	YEAR 2025	Seat color: <u>GRAY</u> Floor color: <u>BLACK</u>	Overall vehicle length (inches): w/o lift <u>479.5</u> w/lift <u>N/A</u>

CHASSIS

MAKE THOMAS BUILT BUS	Warranty: Years <u>1</u> Miles <u>UNLIM</u>
MODEL 380DS	YEAR 2025
Wheelbase: <u>277</u>	

MOTOR

MANUFACTURER PROTERRA	Torque: <u>1200</u> @ _____ RPM
MODEL PRO-DRIVE	YEAR NEW
H.P.: <u>295</u> @ _____ RPM	

BATTERIES

12 Volt	Propulsion
Battery type/grp: <u>31</u> _____	Number batteries: <u>1</u>
Number batteries: <u>2</u>	Total kWh: <u>244</u>
Total CCA: <u>1900</u>	

Warranty: Years <u>5</u>	
Miles <u>100,000</u>	

QUOTED PRICE

Quoted price is based upon payment within 30 days after delivery to the school district (without sales tax).

Bid—w/o lift \$ 489,376.00

Bid—w/lift \$ NO BID

VENDOR REPRESENTATIVE'S SIGNATURE

Scott Meyer

DATE

08/06/2024

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C77 ☒ D84 – ELECTRIC

Use this document to bid both non-lift and lift buses.

PART II

Vendor: SCHETKY NW
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Activity Securement Seating	2-passenger position seats with lap-shoulder belts in all passenger positions.	Passenger Capacity <u>52</u> Cost \$ <u>650.00 PER SEAT, REPLACE STD SEAT</u>	
Air Conditioning	To cool passenger compartment as required in the Washington State School Bus Specifications manual.	Mfr. <u>CARRIER AC-IW10/IW1 120K BTU</u> Cost \$ <u>22,160.00</u>	
Anti-spray Device	Rubber fender extenders.	Type C: Cost \$ <u>195.00</u> Type D: Cost \$ <u>375.00</u>	
Back-up Alarm	Must meet state specification.	Mfr. <u>THOMAS</u> Cost \$ <u>175.00</u>	
Brakes	4-wheel hydraulic disk brake.	Cost \$ <u>N/A</u>	Deduct \$ <u> </u>
Brakes	Air, Drum or Disc. Refer to Washington State School Bus Specifications manual.	Disc Cost \$ <u>4,350.00</u> Drum Cost \$ <u>INCLUDED</u>	Disc Deduct \$ <u>N/A</u> Drum Deduct \$ <u>N/A</u>
Color	Exterior white roof.	Cost \$ <u>790.00</u>	
Door Locks	Vandal lock system on all exterior doors.	Cost \$ <u>350.00</u>	
Driver's Seat	Suspension type, 6-way adjustable, with lumbar adjustment. Cloth panel covers.	Non-Air	Air
		Mfr. <u>N/A</u>	Mfr. <u>INCLUDED</u>
		Cost \$ <u> </u>	Cost \$ <u> </u>
Fire Suppression System	Jomar VT-6-E-NAF, or equal engine compartment fire suppression system of appropriate size to be installed according to manufacturer recommendation.	Mfr. <u>FOGMAKER</u> Cost \$ <u>6,300.00</u>	
Floor Color	Nonstandard color.	Cost \$ <u>950.00</u>	
Headlights	Halogen.	Cost \$ <u>N/A</u>	
Headlights	L.E.D.	Cost \$ <u>INCLUDED</u>	

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C77 ☒ D84 – ELECTRIC

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: SCHETKY NW
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Heater (Auxiliary water)	Auxiliary fuel-fired heating systems. Refer to Washington State School Bus Specifications Manual, page 27.	Brand: <u>N/A</u> Model: _____ Cost \$ _____
Noise Reduction	Exceeding minimum specifications.	Driver compartment Cost \$ <u>250.00</u> Engine compartment Cost \$ <u>INCLUDED</u> Full acoustical headliner Cost \$ <u>990.00</u>
Retarder	Manufacturer's standard.	Driveline ☐ Cost \$ <u>N/A</u> Exhaust ☐ Cost \$ _____ Transmission ☐ Cost \$ _____
Seat Belt Ready Seat	3-passenger position seat with securement belts.	Cost \$ <u>1,225.00</u>
Seating System	Identical, non-lift bus with lap-shoulder seat belt system installed in all positions.	2 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 2 Cost \$ <u>12,718.00</u> Capacity <u>44</u> 3 by 3 Cost \$ <u>16,184.00</u> Capacity <u>84</u>
Storage Compartments	Largest available for unit bid.	Left side <u>21.4</u> cubic feet. Cost \$ <u>1,375.00</u> Right-side <u>21.4</u> cubic feet. Cost \$ <u>1,375.00</u> Push-thru <u>N/A</u> cubic feet. Cost \$ _____
Strobe Light	Exterior roof mounted white strobe light.	Mfr. <u>THOMAS</u> Model No. <u>DOUBLE FLASH</u> Cost \$ <u>295.00</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C77 ☒ D84 – ELECTRIC

Use this document to bid both non-lift and lift buses.

Vendor: SCHETKY NW
SALES
THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.	
Student Protection System—Installed	Electronic system to insure driver post-trip inspection of passenger compartment.	Mfr. <u>THOMAS</u> Model No. <u>PASS-ADVISORY</u> Cost \$ <u>390.00</u>	
Suspension	Air ride (Air brake system only).	Front	Rear
		Cost \$ <u>N/A</u>	Cost \$ <u>4,025.00</u>
Toolbox	Interior, manufacturer standard.	Cost \$ <u>85.00</u>	Deduct \$ <u>N/A</u>
Traction Device	Automatic chains.	Mfr. <u>ON-SPOT</u> Cost \$ <u>4,950.00</u>	
Traction Device	Sanders.	Capacity <u>158-LB</u> Cost \$ <u>6,100.00</u>	
Vehicle Securement System	Must meet state specification.	Mfr. <u>SAFETY BRAKE</u>	Cost \$ <u>2,150.00</u>
Video Camera Systems—Installed	Digital audio/video system for monitoring the passenger compartment with more than two cameras.	Mfr. <u>SEON</u> Model No. <u>DH</u> Cost \$ <u>4,230.00</u> How many cameras <u>3</u>	
Video Camera Systems—Stop Sign Camera—Installed	Must meet state specification.	Stand Alone System	Added to Interior System
		Mfr. <u>SEON</u> Model No. <u>DH</u> Cost \$ <u>4,780.00</u> How many cameras <u>4</u>	Mfr. <u>SEON</u> Model No. <u>DH</u> Cost \$ <u>705.00</u> How many cameras <u>1</u>
Warning Light Monitor	16 light monitoring system.	Incandescent	LED Lights
		Cost \$ <u>N/A</u>	Cost \$ <u>350.00</u>

State Price Quote Specification
DISTRICT-SUPPORTED OPTIONS

☐ C77 ☒ D84 – ELECTRIC

Use this document to bid both non-lift and lift buses.

PART II (cont.)

Vendor: SCHETKY NW

SALES

THOMAS BUILT BUS

ITEM	Vendor must meet or exceed these specifications. Item bid shall be specified in column to right.	VENDOR SPECIFICALLY IDENTIFY ITEM BID Price of items bid will establish the district cost.
Additional Wheelchair/Occupant Tie-down System—Installed	Must meet state specification.	Mfr. <u>N/A</u> Model No. _____ Cost per station \$ _____
Windows	Laminated passenger-compartment side or rear glass.	Side Cost \$ <u>1,500.00</u> Rear Cost \$ <u>INCLUDED INSIDE COST</u> Both Cost \$ <u>1,500.00</u>
Windows	Tinted.	Cost \$ <u>750.00</u>
Windows	Thermal pane, left of driver and service door.	Cost \$ <u>895.00</u>