

LEHDER Environmental Services Limited has attempted to obtain an updated (M)SDS. No update is available for the following reason(s):

Product has been discontinued.

Obsolete (eg. product no longer manufactured under this name, manufactured or distributed by a different company and/or division).

Company no longer exists (sold, merged, receivership, etc.).

Contact information no longer valid.

Consequently no further updates will be issued. This (M)SDS should be used until the product is removed from your facility.

Please advise when product is no longer on site in order to remove it from your inventory.

Material Safety Data Sheet: AEROLEX PLUS AEROSOL

Supercedes Date 06/28/2011 Issuing Date 02/14/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name AEROLEX PLUS AEROSOL Recommended use Lubricant Information on Manufacturer **CERTIFIED LAB PRODUCTS** 239 ORENDA ROAD BRAMPTON ONT L6T 1E6

Product Code 5438 Chemical nature Alcoholic solution **Emergency Telephone Number** CHEMTREC® 800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview DANGER Extremely flammable May be harmful if inhaled May cause skin irritation Causes eye irritation Harmful or fatal if swallowed

Color Dark grav Physical State Liquid **Odor** Alcoholic

Contents under pressure

Potential Health Effects Principle Route of Exposure

Primary Routes of Entry

Acute Effects

Inhalation, Skin contact, Eye contact.

Inhalation, Skin Absorption.

Eyes Causes eye irritation.

Skin May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Inhalation May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May

cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue,

muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes headache,

drowsiness or other effects to the central nervous system. Aspiration hazard if swallowed - can enter

lungs and cause damage. May be fatal if swallowed and enters airways.

Chronic Toxicity Ingestion may cause lowering of blood pressure. Liver and kidney injuries may occur. Contains a

known or suspected reproductive toxin.

Target Organ Effects

Aggravated Medical Conditions

Respiratory system, Central nervous system, Liver, Kidney, Heart, Blood, Skin, Eyes, Bone, Ears. Respiratory disorders, Skin disorders, Liver disorders, Kidney disorders, Blood disorders,

Neurological disorders, Heart disease.

See Section 12 for additional Ecological information. **Potential Environmental Effects**

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No
Isopropyl alcohol	67-63-0
Butane	106-97-8
Propane	74-98-6
Molybdenum disulfide	1317-33-5
Ethylcellulose	9004-57-3
Pseudocumene	95-63-6
Urea	57-13-6
Petroleum naphtha, light aromatic	64742-95-6
1,3,5-Trimethylbenzene	108-67-8
Xylenes (o-, m-, p- isomers)	1330-20-7

4. FIRST AID MEASURES

General advice Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.

Eve Contact Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops

and persists.

Skin Contact Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and

persists.

If inhaled, remove to fresh air. Get medical attention if symptoms occur. Inhalation

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give

anything by mouth to an unconscious person.

Notes to physician

Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

5. FIRE-FIGHTING MEASURES

Flash Point $47 \, ^{\circ}\text{F} \, / \, 8 \, ^{\circ}\text{C}$ Method Seta closed cup

Autoignition Temperature No information available.

Flammability Limits in Air % Mixture. Upper 12.7 Lower 1.8

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Foam. Dry chemical.

Specific hazards arising from the chemical

Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >36 inches / >91.4 cm and Burnback: 6 inch / 15 cm.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) - 3

NFPA Health 2 Flammability 4 Instability 0 HMIS Health 2 Flammability 4 Instability 0 Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment.

Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.

Environmental PrecautionsDo not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous

earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see

section 13)

Methods for Cleaning Up

Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled

containers.

Neutralizing Agent Not applicable.

7. HANDLING AND STORAGE

Handling Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing vapors, mist or

gas. Avoid contact with skin, eyes and clothing.

Storage Keep away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Isopropyl alcohol	TWA: 200 ppm	TWA: 400 ppm	IDLH: 2000 ppm
	STEL: 400 ppm	TWA: 980 mg/m ³	STEL 500 ppm
			STEL 1225 mg/m ³
			TWA: 400 ppm
			TWA: 980 mg/m ³
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm
			TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
		TWA: 1800 mg/m ³	TWA: 1000 ppm
		-	TWA: 1800 mg/m ³
Molybdenum disulfide	TWA: 10 mg/m ³	TWA: 15 mg/m ³	IDLH: 5000 mg/m ³
	TWA: 3 mg/m ³		
Ethylcellulose	No data available	No data available	No data available
Pseudocumene	No data available	No data available	TWA: 25 ppm
			TWA: 125 mg/m ³
Urea	No data available	No data available	No data available
Petroleum naphtha, light aromatic	No data available	No data available	No data available
1,3,5-Trimethylbenzene	No data available	No data available	TWA: 25 ppm
			TWA: 125 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm	TWA: 100 ppm	No data available
	STEL: 150 ppm	TWA: 435 mg/m ³	

Engineering Measures
Personal Protective Equipment

Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

Eye/Face Protection Safety glasses with side-shields.

Skin Protection Wear suitable protective clothing, Impervious gloves.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations

above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Ensure that eyewash stations and safety showers are close to the workstation location. Remove and

wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid Slightly Viscous **Physical State** Viscosity Color Dark gray Odor Alcoholic рΗ **Appearance** Opaque Not applicable **Specific Gravity** 0.708 **Evaporation Rate** 51.5 (Butyl acetate=1)

Percent Volatile (Volume) 98.7 VOC Content (%) 95

VOC Content (g/L) 672 Vapor Pressure 1323 mmHg @ 70°F

Vapor Density 1.9 (Air = 1.0) Solubility Dispersible

Boiling Point/Range 180 °F / 82 °C

10. STABILITY AND REACTIVITY

Chemical Stability Conditions to Avoid Incompatible Products

Hazardous Decomposition Products Possibility of Hazardous Reactions

Stable. Hazardous polymerization does not occur.

Keep away from open flames, hot surfaces, and sources of ignition Strong oxidizing agents, Acids, Bases, Aldehydes, Ketones, Halogenated

hydrocarbon.

Carbon oxides, Nitrogen oxides (NOx), Sulfur oxides.

None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Isopropyl alcohol	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rabbit)	= 16000 ppm (Rat) 8 h	no data available	no data available
Butane	no data available	no data available	= 658 g/m ³ (Rat) 4 h	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Molybdenum disulfide	no data available	no data available	> 2820 mg/m ³ (Rat) 4 h	no data available	no data available
Ethylcellulose	no data available	no data available	no data available	no data available	no data available
Pseudocumene	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h	no data available	no data available
Urea	14,300-15,000 mg/kg (rat)	no data available	no data available	no data available	no data available
Petroleum naphtha, light aromatic	no data available	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h =	no data available	no data available
			3400 ppm (Rat) 4 h		
1,3,5-Trimethylbenzene	no data available	no data available	= 24 g/m ³ (Rat) 4 h	no data available	no data available
Xylenes (o-, m-, p- isomers)	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Isopropyl alcohol	no data available	no data available	no data available	no data available	eyes, respiratory system, skin, liver, kidney, CNS
Butane	no data available	no data available	no data available	no data available	CNS, heart
Propane	no data available	no data available	no data available	no data available	CNS, heart
Molybdenum disulfide	no data available	no data available	no data available	no data available	respiratory system, kidneys, eyes, blood, bones, joints
Ethylcellulose	no data available	no data available	no data available	no data available	no data available
Pseudocumene	no data available	no data available	no data available	no data available	eyes, CNS, respiratory system, skin, blood, ears, heart
Urea	no data available	no data available	no data available	no data available	no data available
Petroleum naphtha, light aromatic	no data available	no data available	no data available	no data available	CNS
1,3,5-Trimethylbenzene	no data available	no data available	no data available	no data available	eyes, CNS, respiratory system, skin, blood, ears, heart
Xylenes (o-, m-, p- isomers)	no data available	no data available	yes	no data available	heart, lung, CNS, PNS, respiratory system, ears, liver, kidney

Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Other
Isopropyl alcohol	not applicable				
Butane	not applicable				
Propane	not applicable				
Molybdenum disulfide	not applicable				
Ethylcellulose	not applicable				
Pseudocumene	not applicable				
Urea	not applicable				
Petroleum naphtha, light aromatic	not applicable				
1,3,5-Trimethylbenzene	not applicable				
Xylenes (o-, m-, p- isomers)	not applicable				

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Isopropyl alcohol	EC50 > 1000 mg/L	LC50 = 9640 mg/L Pimephales	EC50 = 35390 mg/L 5 min	EC50= 13299 mg/L 48 h	0.05
	Desmodesmus	promelas 96 h			
	subspicatus 96 h	LC50 = 11130 mg/L Pimephales			
	EC50 > 1000 mg/L	promelas 96 h			
	Desmodesmus	LC50 > 1400000 µg/L Lepomis			
	subspicatus 72 h	macrochirus 96 h			
Butane	no data available	no data available	no data available	no data available	2.89
Propane	no data available	no data available	no data available	no data available	2.3
Molybdenum disulfide	no data available	no data available	no data available	no data available	N/A
Ethylcellulose	no data available	no data available	no data available	no data available	N/A
Pseudocumene	no data available	LC50 7.19 - 8.28 mg/L Pimephales	no data available	EC50= 6.14 mg/L 48 h	3.63
		promelas 96 h		-	
Urea	no data available	LC50 16200 - 18300 mg/L Poecilia	EC50 = 23914 mg/L 5 min	EC50> 10000 mg/L 24 h	-1.59
		reticulata 96 h		EC50= 3910 mg/L 48 h	
Petroleum naphtha, light aromatic	no data available	LC50 = 9.22 mg/L Oncorhynchus	no data available	EC50= 6.14 mg/L 48 h	N/A
		mykiss 96 h		-	
1,3,5-Trimethylbenzene	no data available	LC50 = 3.48 mg/L Pimephales	no data available	EC50= 50 mg/L 24 h	N/A
		promelas 96 h			
Xylenes (o-, m-, p- isomers)	no data available	LC50 = 13.4 mg/L Pimephales	EC50 = 0.0084 mg/L 24 h	EC50= 3.82 mg/L 48 h	2.77 - 3.15
		promelas 96 h		LC50= 0.6 mg/L 48 h	
		LC50 2.661 - 4.093 mg/L			
		Oncorhynchus mykiss 96 h			
		LC50 13.5 - 17.3 mg/L Oncorhynchus			
		mykiss 96 h			
		LC50 13.1 - 16.5 mg/L Lepomis			
		macrochirus 96 h			
		LC50 = 19 mg/L Lepomis macrochirus			
		96 h			
		LC50 7.711 - 9.591 mg/L Lepomis			
		macrochirus 96 h			
		LC50 23.53 - 29.97 mg/L Pimephales			
		promelas 96 h			
		LC50 = 780 mg/L Cyprinus carpio 96			
		n LC50 > 780 mg/L Cyprinus carpio 96			
		b			
		LC50 30.26 - 40.75 mg/L Poecilia			
		reticulata 96 h			
		icticulata 90 II			

Persistence and Degradability Bioaccumulation Mobility

No information available. No information available. No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Container Disposal Dispose of in accordance with local regulations.

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Consumer commodity

Hazard Class ORM-D

Description Consumer commodity ,ORM-D,

TDG

Proper shipping name Aerosols
Hazard Class 2.1
UN-No UN1950

Description AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO

UN-No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

Shipping Description Aerosols,UN1950 2.1 LTD. QTY.

IATA

UN-No UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1 ERG Code 10L

Shipping Description UN1950, Aerosols, flammable, 2.1 LTD. QTY.

IMDG/IMO

Proper Shipping NameAerosolsHazard Class2UN-NoUN1950EmS No.F-D, S-U

Shipping Description UN1950, Aerosols, 2.1 LTD QTY.

15. REGULATORY INFORMATION

Inventories

TSCA Complies DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Isopropyl alcohol	67-63-0	40-70	1.0
Pseudocumene	95-63-6	1-5	1.0
Xylenes (o-, m-, p- isomers)	1330-20-7	0.1-1	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of	Reactive Hazard
			Pressure Hazard	
Yes	Yes	Yes	Yes	No

CERCLA		
Component	Hazardous Substances RQs	CERCLA EHS RQs
Isopropyl alcohol	Not applicable	Not applicable
Butane	Not applicable	Not applicable
Propane	Not applicable	Not applicable
Molybdenum disulfide	Not applicable	Not applicable
Ethylcellulose	Not applicable	Not applicable
Pseudocumene	Not applicable	Not applicable
Urea	Not applicable	Not applicable
Petroleum naphtha, light aromatic	Not applicable	Not applicable
1,3,5-Trimethylbenzene	Not applicable	Not applicable
Xylenes (o-, m-, p- isomers)	100 lb	Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases B5 Flammable aerosol D2B Toxic materials



16. OTHER INFORMATION

Prepared By Angela Hutson Supercedes Date 06/28/2011 Issuing Date 02/14/2014

Reason for RevisionNo information available.GlossaryNo information available.List of References.No information available.

CERTIFIED LAB PRODUCTS assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.